



END VIEWS / DIMENSIONS



FLEXIBLE CHANNEL (12" Minimum Bend Radius)



Surface Mounted Flex



Horizontal Mounted Flex

Note: For best results, only bend channel once. Do not bend back and forth. Best used for long, sweeping arcs. Not suitable for tight corners.

LENS / OPTICS APPEARANCE



Clear Lens (CL)
Visible Diode Image
0% Light Loss



50% Semi-Frosted Lens (SF)
Slight Diode Image
12.5% Light Loss



100% Frosted Lens (F)
No Diode Image: Line of Light
25% Light Loss


GENERAL FEATURES

Applications	Accent, Decorative, Surface, Recess, Pendant Lighting
Lens	Clear, 50% Semi-Frosted, or 100% Frosted
Viewing Angle	120°
Length	Built to Order (+/- 1/8" Tolerance)
Construction	Aluminum Extrusion
Weight	0.078 lbs per foot
Mounting	Mounting Channel or Mounting Clips (Sold Separately)
Listing	Dry, Wet, or IP67 Location UL2108, 67.1.9, 60.4, CSA C22.2 #9 UL8750, CSA250
Driver	Remote (Sold Separately)
Temperature Ratings	Operating / Startup: -20° to 48°C (-4° to 120°F) Storage: -40° to 76°C (-40° to 170°F)
Installation Link	

ELECTRICAL

Dimming	DMX
Maximum Run (Class 1 Applications)	26' (4.5W) 33' (3.6W)
Maximum Run (Class 2 Applications)	21' (4.5W) 26' (3.6W)
Luminaire Voltage	24VDC

BEAM ANGLE



120° x 120° Beam

SPECIFY PRODUCT CODE | CHOOSE FROM DROP DOWNS

Series	Lens	Watts per Foot	Dimming	LED	Listing	Finish	Luminaire Length
A8-ZUDA-SFX			DMX	DWH			
ZUDA Standard Flex (A8-ZUDA-SFX)	Clear Lens (CL)	3.6 Watts (3.6W)	DMX-512*1 (DMX)	2400K - 6400K (DWH)	Indoor (DRY)	Natural Silver*3 (NA)	Specify Length in Feet & Inches Example: 7'8"
	50% Semi-Frosted Lens (SF)	4.5 Watts (4.5W)			Outdoor*2 (WET)	Polished (PA) White (WH)	
	100% Frosted Lens (F)				Outdoor IP67*2 (IP67)	Satin / Silver (SA) Black (BK)	

*1 Default DMX address of each luminaire is 001. Consult third party DMX commissioner to modify at time of installation.

*2 Run lengths are required for Wet & IP67 Location products. Provide run lengths at time of order.

*3 Default finish is Natural Silver (NA) if left blank.



LAMP SPECIFICATIONS

Lamp Number	Correlated Color Temperature (CCT) Gamut	L70 LED Life
DWH	Dynamic White: 2400K - 6400K	50,000 hrs.

LAMP FEATURES


Lamp Type	Dynamic White LEDs: 2400K - 6400K
CRI	> 90

DRIVERS

Dimming Selection	Product Code	Link to Specification Sheet / URL
DMX-512*5	(DMX)	

MOUNTING OPTIONS (Sold Separately)


Note: Mounting clips are only available in Natural Silver Finish, unless otherwise specified.



Part #	Qty.
A8-ZUDA-SFX-MC	

Note: Use 1 mounting clip per 2', rounded up.
Click on image to see cut sheet for additional details.

DMX CONTROLLERS (Sold Separately)



Part #	Qty.
DRV100-E-UNV-24VDC-DMX-DRY	

Note: Use 1 Driver / Decoder for each run up to 100 Watts.



Part #	Qty.
CTRL-DMX-RGBX	

Note: Use 1 Decoder for each run up to 96 Watts. Not required if using all-in-one driver / decoder (DRV100-E).



Part #	Qty.
CTRL-DMX-128C	


Note: Controls up to 128 DMX Channels.



Part #	Qty.
CTRL-DMX-1024C	


Note: Controls up to 1024 DMX Channels.

DRY CONNECTORS (Sold Separately)



Part #	Length	Qty.
A8-PC-3P-DRY-	36"	
A8-PC-3P-DRY-		

Note: Connector style subject to change without notice. Refer to cut sheet for wiring colors.




Part #	Length	Qty.
A8-CC-3P-DRY-	3"	
A8-CC-3P-DRY-		

Note: Connector style subject to change without notice. Refer to cut sheet for wiring colors.




DESIGN GUIDELINES


Individual Fixture




Continuous Run (Dry or Wet Location)




Runs with Continuous Connector (Dry Location)



Runs with Continuous Connector (Wet Location)



Runs with Continuous Connector (Wet Location)




KEY

- Detail A Two Extrusions Meet:** Two extrusion segments meet, held together by a mounting clip. Refer to installation instructions for additional details.
- Detail B Two Lenses Meet:** Lenses are staggered so that the lens always overlaps where two extrusion segments meet. Refer to installation instructions for additional details.
- Detail C Flexible Channel:** The channel is able to vertically bend around curves and contour to the installation area.
- Detail D Dry Continuous Connector:** Used to span a corner or traverse a gap, corner, or obstacle in a dry location installation area.
- Detail E Wet Continuous Connector:** Used to span a corner or traverse a gap, corner, or obstacle in a wet location installation area.

Note: Drawings not to scale. Product may differ from examples shown.

CONNECTION SEQUENCE




- Specifying a layout is not required to place an order.
- Configuration code applies to full length ordered and will be built per the Continuous Run models on Design Guidelines.
- Connector type subject to change based on availability and listing. Refer to Design Guidelines for details.

HOW TO SPECIFY CONFIGURATIONS


Example: 20' Straight Run

- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-DRY-NA-20'-PC-EC




Example: 25' L-Shaped Run

- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-WET-NA-12'-PC-CC
- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-WET-NA-6'-CC-EC



Example: 30' U-Shaped Run

- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-DRY-NA-6'-PC-CC
- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-DRY-NA-18'-CC-CC
- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-DRY-NA-6'-CC-EC



Example: 28' Rectangle Shaped Run

- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-WET-NA-11'-PC-CC
- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-WET-NA-3'-CC-CC
- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-WET-NA-11'-CC-CC
- 1x A8-ZUDA-SFX-CL-3.6W-DMX-DWH-WET-NA-3'-CC-EC

