


### GENERAL FEATURES

<b>Applications</b>	Accent, Decorative, Surface, Recessed, Pendant Lighting
<b>Lens</b>	Clear, 50% Semi-Frosted, or 100% Frosted
<b>Viewing Angle</b>	120°
<b>Length</b>	Built to Order (+/- 1/8" Tolerance)
<b>Construction</b>	Aluminum Extrusion
<b>Field Cutting</b>	Dry and Wet Location Field Cuttable
<b>Weight</b>	0.378 lbs per foot
<b>Mounting</b>	Mounting Brackets (Sold Separately)
<b>Driver</b>	Remote (Sold Separately)
<b>Listing</b>	Dry, Wet, or IP67 Location UL2108, 67.1.9, 60.4, CSA C22.2 #9 UL8750, CSA250
<b>Temperature Ratings</b>	Operating / Startup: -20° to 48°C (-4° to 120°F) Storage: -40° to 76°C (-40° to 170°F)
<b>Installation Link</b>	

### ELECTRICAL

<b>Dimming</b>	0-10V
<b>Maximum Run (Class 2 Applications)</b>	19' (4.3W)
<b>Luminaire Voltage</b>	24VDC

### END VIEWS / DIMENSIONS



### SPECIFY PRODUCT CODE | CHOOSE FROM DROP DOWNS

Series	Lens	Watts per Foot	Dimming	LED	Listing	Finish	Luminaire Length
<b>A8-ZYPO-ROD</b>		<b>4.3W</b>	<b>10V</b>	<b>DWM</b>			
ZYPO Pendant Rod (A8-ZYPO-ROD)	Clear Lens (CL)	4.3 Watts (4.3W)	0-10V: 100% - 1% (10V)	Dim to Warm: 3000K - 2200K (DWM)	Indoor (DRY)	Natural Silver* <sup>2</sup> (NA)	Specify Length in Feet & Inches Example: 7'8"
	50% Semi-Frosted Lens (SF)				Outdoor* <sup>1</sup> (WET)	Polished (PA) White (WH)	
	100% Frosted Lens: Line of Light (F)				Outdoor IP67* <sup>1</sup> (IP67)	Satin / Silver (SA) Black (BK)	

\*<sup>1</sup> Run lengths are required for Wet & IP67 Location products. Provide run lengths at time of order.

\*<sup>2</sup> Default finish is Natural Silver (NA) if left blank.



## A8 Series | LED Tape

### ZYPO Pendant Rod


(A8-ZYPO-ROD)

TYPE

#### LAMP FEATURES

Lamp Type	Dim to Warm LEDs
CRI	> 90
Efficacy	148 Lumens per Watt @ 25% 137 Lumens per Watt @ 50% 118 Lumens per Watt @ 75% 92 Lumens per Watt @ 100%

#### BEAM ANGLE



#### LAMP SPECIFICATIONS

Lamp Number	Correlated Color Temperature (CCT) @ Dimming Percentage	L70 LED Life
DWM	2400 Kelvin @ 25%	60,000 hrs.
	2600 Kelvin @ 50%	
	2800 Kelvin @ 75%	
	3000 Kelvin @ 100%	

#### LENS / OPTICS APPEARANCE



Clear Lens (CL)  
Visible Diode Image  
0% Light Loss



50% Semi-Frosted Lens (SF)  
Slight Diode Image  
12.5% Light Loss




100% Frosted Lens (F)  
No Diode Image: Line of Light  
25% Light Loss

#### DRIVERS

Dimming Selection	Product Code	Link to Specification Sheet / URL
0-10V: 100% - 1%	(10V)	

#### MOUNTING OPTIONS (Sold Separately)

**Note:** Mounting clips are only available in Natural Silver Finish, unless otherwise specified.



Part #	Qty.
A8-ZYPO-ROD-MB	

**Note:** Use 1 mounting bracket per 2', rounded up.  
Click on image to see cut sheet for additional details.




End Cap  
(A8-ZYPO-ROD-EC)

Part #	Qty.
A8-ZYPO-ROD-EC	


**Note:** Use 1 End Cap for each run termination.

### DRY CONNECTORS (Sold Separately)


**Note:** Connector style subject to change without notice. Refer to cut sheet or installation instructions for wiring colors.




Part #	Length	Qty.
A8-PC-2P-DRY-	36"	
A8-PC-2P-DRY-		




Part #	Length	Qty.
A8-PC-2P-DRY-BK-	36"	
A8-PC-2P-DRY-BK-		




Part #	Length	Qty.
A8-PC-2P-DRY-WH-	36"	
A8-PC-2P-DRY-WH-		



Part #	Length	Qty.
A8-CC-2P-DRY-	3"	
A8-CC-2P-DRY-		




Part #	Length	Qty.
A8-CC-2P-DRY-BK-	3"	
A8-CC-2P-DRY-BK-		




Part #	Length	Qty.
A8-CC-2P-DRY-WH-	3"	
A8-CC-2P-DRY-WH-		

### WET CONNECTORS (Sold Separately)


**Note:** Connector style subject to change without notice. Refer to cut sheet or installation instructions for wiring colors.



Part #	Length	Qty.
A8-PC-2P-WET-	36"	
A8-PC-2P-WET-		




Part #	Length	Qty.
A8-CC-2P-WET-	3"	
A8-CC-2P-WET-		




Part #	Length	Qty.
A8-SC-2P-WET		

### DESIGN GUIDELINES

#### Individual Fixture



#### Continuous Run (Dry or Wet Location)



### KEY

- Detail A Mounting Bracket:** Mounting Brackets are used to suspend the closet rod extrusion in place and provide support for the weight of hanging items.
- Detail B End Cap:** End Caps support the run at each end and provide an entrance for power leads.
- Detail C Two Lenses Meet:** Lenses are staggered so that the lens always overlaps where two extrusion segments meet. Refer to installation instructions for additional details.
- Detail D Two Extrusions Meet:** Two extrusion segments meet. Refer to installation instructions for additional details.

**Note:** Drawings not to scale. Product may differ from examples shown.